



Ilargi Ø395

Iratzoki-Lizaso

Pendant Ilargi Ø395 LED 25.5 LED warm-white 2700K 1-10V Madera Oscura 1507lm

Technical features

Luminaire total power: 25.5W
Real lumens: 1507
Real lm/W: 59
Correlated Colour Temperature (CCT): LED warm-white 2700K
UGR: <=16
Structure material: Wood, Steel
Structure finish: Madera Oscura
Diffuser material: Glass
Diffuser finish: Opal
Driver Brand: HEP
Voltage / frequency: 100-240V/50-60Hz
Dimming protocol: 1-10V
Power Factor: 0.90
THD%: 15
Useful life: 50,000h L80B20
Warranty: 5 años
Easily recyclable luminaire



Luminotechnic features

Luminance C0°G65°: 933
Luminance C90°G65°: 933
CRI: 90
MacAdam steps: 3
Photobiological risk: RG2

UGR		Lampholder	Quantity	Light source power (W)	Correlated Colour Temperature (CCT)
S=0.250					
Ceiling / cavity	0.7	LED	1	21.4W	LED warm-white 2700K
Walls	0.5				
Working Plane	0.2				
Room dimensions	X=4H, Y=8H				
UGR crosswise	15.5				
UGR lengthwise	15.5				





Image may not match reference. LedsC4 reserves the right to amend any of the product's components. The data related to flux, power and colour temperature may be subject to changes made by the manufacturer.



Ilargi Ø395

Iratzoki-Lizaso

Pendant Ilargi Ø395 LED 25.5 LED warm-white 2700K 1-10V Madera Oscura 1507lm

Light application



Image may not match reference. LedsC4 reserves the right to amend any of the product's components. The data related to flux, power and colour temperature may be subject to changes made by the manufacturer.